


Pressure Ratings

Standard Construction
Bulletin 3000

DEMING®

www.cranepumps.com

End Suction Pumps

		A48 - CLASS 30 CAST IRON		A536 65 - 45 - 12 DUCTILE IRON	
		FLANGE CLASS RATING PSI	MAXIMUM CASING WORKING PRESSURE PSI *	FLANGE CLASS RATING PSI	MAXIMUM CASING WORKING PRESSURE PSI *
PUMP SIZE	SIZE CODE	SUCTION / DISCHARGE		SUCTION / DISCHARGE	
1½ x 1 x 6	101	125	175	-	-
2 x 1½ x 6	151	125	175	-	-
3 x 2 x 6	201	125	175	-	-
4 x 3 x 6	301	125	175	-	-
3 x 2½ x 7	252	125	175	-	-
1½ x 1 x 8	102	125	175	-	-
2 x 1½ x 8	152	125	175	-	-
3 x 2 x 8	202	125	175	-	-
4 x 3 x 8	302	125	175	-	-
6 x 4 x 8	402	125	175	300	450
2 x 1 x 10	103	125	175	-	442
2 x 1½ x 10	153	125	175	-	442
3 x 2 x 10	203	125	175	-	404
3 x 2 x 10H	213	125	175	-	404
4 x 3 x 10	303	125	175	300	450
4 x 3 x 10H	313	125	175	-	436
5 x 4 x 10	403	125	175	300	395
6 x 4 x 10	403	125	175	300	367
8 x 6 x 10	603	125	175	300	450
3 x 2 x 13	204	125	175	300	450
4 x 3 x 13	304	125	175	300	433
6 x 4 x 13	404	125	175	300	450

* Pressure Rating is for Cold Water at 100° F.

SECTION 3120
PAGE 10
DATE 10/18

CRANE
A Crane Co. Company

PUMPS & SYSTEMS

USA: (937) 778-8947 • Canada: (905) 457-6223 • International: (937) 615-3598