

MODEL TD Control Panel


Single phase, simplex timed dosing pump control.

The Model TD control panel provides a reliable means of controlling one single phase pump in onsite septic installations. A programmable timer activates a magnetic motor contactor to turn the pump on and off. A low level cutout float overrides the timer to prevent the pump from running dry. An alarm float activates the audio/visual alarm system indicating a high liquid level. Common applications include sand filter systems, pressure distribution systems, mound systems, or any application requiring a timed dose.

PANEL COMPONENTS

1. **Enclosure** measures 10 x 8 x 4 inches (25.40 x 20.32 x 10.16 cm) NEMA 4X (ultraviolet stabilized thermoplastic with removable mounting feet for outdoor or indoor use).
2. **Magnetic Motor Contactor** controls pump by switching electrical lines.
3. **HOA Switch** for manual pump control.
4. **Control Fuse**
5. **Alarm Fuse**
6. **Float Switch Terminal Block**
7. **Incoming Power Terminal Block**
8. **Programmable Timer** with separate variable controls allows for setting the on and off times from .05 seconds to 30 hours.
9. **Circuit Breaker** provides pump disconnect and branch circuit protection.
10. **Spare Fuse**
11. **Backplate Label** includes diagram of float, pump, and power connections.
12. **Ground Lug**

NOTE: Timer Installation Label and Pump/Float Switch Installation Specification Label are located inside the panel on enclosure cover.



Model Shown TD1W914X

STANDARD ALARM PACKAGE

13. **Red Alarm Beacon** provides 360° visual check of alarm condition.
14. **Alarm Horn** provides audio warning of alarm condition (83 to 85 decibel rating).
15. **Exterior Alarm Test/Normal/Silence Switch** allows horn and light to be tested and horn to be silenced in an alarm condition. Alarm automatically resets once alarm condition is cleared.
16. **Horn Silence Relay** (mounted under bracket).

NOTE: other options available.



FEATURES

- Entire control system (panel and switches) is UL Listed to meet and/or exceed industry safety standards
- Dual safety certification for the United States and Canada
- Standard package includes two 20' float switches
- Available with EZconnex® float system
- Complete with step-by-step installation instructions
- Five-year limited warranty

OPTIONAL FEATURE

- **34" (86.36cm) Panel Mounting Post** (Factory Installed). Includes Duplex Installation Kit (Enclosure upsized to 10" x 8" x 6" (25.4 x 20.32 x 15.24 cm). Max. Enclosure size 14" x 12" x 6" (35.56 x 30.48 x 15.24 cm)




SJE RHOMBUS

PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax

email: customer.service@sjerhombus.com

www.sjerhombus.com B.61

**SEE BACKSIDE FOR COMPLETE LISTING OF AVAILABLE OPTIONS.
SEE PRICE BOOK FOR LIST PRICE.**



MODEL TD

ALARM PACKAGE

- 0 = select option (If you select "0", you must select option 1F)
- 1 = alarm package (includes test/normal/silence switch, red beacon, horn)

ENCLOSURE RATING

- W = Weatherproof, NEMA 4X (engineered thermoplastic)

STARTING DEVICE

- 1 = magnetic motor contactor 120/208/240V
- 9 = magnetic motor contactor 120V only

PUMP FULL LOAD AMPS

- 0 = 0-7 FLA
- 1 = 7-15 FLA
- 2 = 15-20 FLA

PUMP DISCONNECTS

- 4 = circuit breaker

FLOAT SWITCH APPLICATION

- H = 20' low level cutout (select 17 or 21 option)
- E = EZconnex® float switch system (select 33, 35 or 36 option)
- X = no floats

OPTIONS *Listed below*

- | CODE | DESCRIPTION |
|------------------------------|---|
| <input type="checkbox"/> 1F | Door mounted alarm indicator with horn and test/normal/silence switch
<i>(must select "0" as an alarm package)</i> |
| <input type="checkbox"/> 4B | Red redundant off indicator and alarm
<i>(must select option "4D" if floats included)</i> |
| <input type="checkbox"/> 4D | Redundant off float |
| <input type="checkbox"/> 4E | Redundant off float, alarm activation
(20' SJE PumpMaster® SPDT) |
| <input type="checkbox"/> 6A | Auxiliary alarm contact, form A |
| <input type="checkbox"/> 8A | Elapsed time meter |
| <input type="checkbox"/> 8C | Event (cycle) counter |
| <input type="checkbox"/> 10E | Lockable latch |
| <input type="checkbox"/> 10K | Anti-condensation heater |
| <input type="checkbox"/> 10P | Panel Mounting Post (Factory Installed. Includes Duplex Install. Kit)(Encl. upsized to 10x8x6.Max 14x12x6) |
| <input type="checkbox"/> 16A | 10' cord in lieu of 20' <i>(per float)</i> |
| <input type="checkbox"/> 16B | 15' cord in lieu of 20' <i>(per float)</i> |
| <input type="checkbox"/> 16C | 30' cord in lieu of 20' <i>(per float)</i> |
| <input type="checkbox"/> 16D | 40' cord in lieu of 20' <i>(per float)</i> |
| <input type="checkbox"/> 17E | Sensor Float® Mini (redundant off, high level alarm)
▲ <i>(per float)</i> |
| <input type="checkbox"/> 18A | Timer override float
(20' SJE PumpMaster®) ● |
| <input type="checkbox"/> 19X | Door mounted pump run indicator |
| <input type="checkbox"/> 21E | SJE PumpMaster® (redundant off, high level alarm)
● <i>(per float)</i> |

- | CODE | DESCRIPTION |
|------------------------------|--|
| <input type="checkbox"/> 33U | EZconnex® 3-Port, 50', w/10' floats (3) / pipe clamp ** |
| <input type="checkbox"/> 35D | EZconnex® 4-Port, 25', w/10' floats (4) / pipe clamp * |
| <input type="checkbox"/> 35E | EZconnex® 4-Port, 50', w/10' floats (4) / pipe clamp * |
| <input type="checkbox"/> 35G | EZconnex® 4-Port, 25', w/20' floats (4) / pipe clamp * |
| <input type="checkbox"/> 35H | EZconnex® 4-Port, 50', w/20' floats (4) / pipe clamp * |
| <input type="checkbox"/> 36D | EZconnex® 3-Port, 25', w/10' floats (2) / pipe clamp, sealing plug * |
| <input type="checkbox"/> 36E | EZconnex® 3-Port, 50', w/10' floats (2) / pipe clamp, sealing plug * |
| <input type="checkbox"/> 36G | EZconnex® 3-Port, 25', w/20' floats (2) / pipe clamp, sealing plug * |
| <input type="checkbox"/> 36H | EZconnex® 3-Port, 50', w/20' floats (2) / pipe clamp, sealing plug * |

- Mechanically-activated ▲ Mercury-activated * EZconnex® mechanically-activated, narrow angle float switches with quick release connections
- ** EZconnex® mechanically-activated, wide angle float switches with quick release connections.